

# Torridon QSFP Cable Pull Module



Hot-Swap automation for QSFP Cables



Data Sheet

## Reduce Time to Market

Cut time to market by 20% for new products by automating manual test procedures

## Reduce Capital Costs

Faster and more detailed testing with Torridon means fewer test systems are required in the lab

## Reduce Human Error

Removing human intervention during tests increases consistency and results in far fewer mistakes. Test scripting provides logging and 100% repeatability

## Increase Product Reliability

Advanced techniques, such as bounds testing and fault injection provide a higher level of confidence and reduced field returns

### **Torridon Cable Pull Modules:**

Automated solution for Cable Pull / Push and Fault Injection. Cable Pull Modules vastly reduce test duration and introduce a level of repeatability and precision that is impossible during manual tests.

### **Complete Automation:**

Any test that requires manual intervention to pull or plug a drive can now be fully automated.

### **Simple Integration:**

The Torridon System works with your existing automated test setup and integrates with minimal effort. A simple command set allows for easy scripting. Quarch provides full support as standard while you get started

### **Who Can Benefit?**

- Enclosure Manufacturers
- Silicon Manufacturers
- Storage System Integrators
- RAID Developers
- Qualification Labs

# Torridon QSFP Cable Pull Module

## Interface Specification

### Power

- ▶ Supplied from Torridon Interface Card or Array Controller

### Comms

- ▶ USB/Serial/Telnet options - As provided by your chosen interface option.

## Cable Compatability

### Sizes

- ▶ Compatible with single QSFP cages. 23mm module width may interfere with ganged cages.

### Speeds

- ▶ Up to 6Gb/s data rates\*

## Glitching

### Timing

- ▶ Glitch any combination of signals with pulses down to 50nS

### Sequences

- ▶ Run glitches in sequences and PRBS patterns

## Physical Dimensions

### QTL1366

- ▶ Width 23 mm
- ▶ Offset ~60 mm

## Timing Specification

### Timers

- ▶ 6 Independent timers for multi stage hot-swap

### Timing resolution

- ▶ 1mS

### Pin-bounce resolution

- ▶ 10uS

### Pin-bounce modes

- ▶ Constant Frequency
- ▶ User defined 112 bit pattern

## Fault Injection

- ▶ Override cable EEPROM data

### SAS Errors

- ▶ Create Framing Errors
- ▶ Force SAS Identify Sequence
- ▶ Fault one side of a pair
- ▶ Fault entire lanes
- ▶ Create random disruption

## Switching

### Switches

- ▶ High Speed RF switches
- ▶ Low insertion loss

### Switched Pins

- ▶ All Data, Power and Management Interface pins may be switched independently

## Support and Utilities

Phone and email support direct to the engineers as standard

'TestMonkey' GUI for rapid test prototyping, script generation and bench testing

## Ordering Information

QTL1366 - Standard Module

### Single units

- ▶ Ideal for bench testing, debugging and evaluation

### Multiple units

- ▶ Run from a Torridon Array Controller for synchronized testing of larger storage systems

## Quarch Technology Ltd

### UK Sales / Technical Enquiries

+44 1343 508 140

enquiries@quarch.com

### US Sales Office

+1 617 245 0528

us\_enquiries@quarch.com

<http://www.quarch.com>

\* Currently qualified at 6Gb/s, performance up to 12Gb/s and beyond tbd